

**StreamJet**® SJ-3 Fertilizer Nozzles



**Features:**

- VisiFlo® color-coding system.
- 3 solid streams of equal velocity and capacity.
- Removable metering orifice for easy cleaning.
- Ten sizes for a wide range of application rates.
- Equally spaced distribution at 20" (50 cm) height.
- Use with Quick TeeJet® cap 25598\*-NYR.
- All acetal construction for excellent chemical resistance.
- See page 154 for liquid density conversion factors.
- Recommended operating pressure: 20-60 PSI (1.5-4 bar).

**How to order:**  
Specify tip number.  
Example:  
SJ3-03-VP – Polymer with VisiFlo color-coding



**NOZZLES**

**HOW TO ORDER: Example**

TJ/	Description	Price
SJ3-xx-VP	SJ-3 StreamJet Nozzles	8.57

Nozzle Icon	PSI	CAPACITY ONE NOZZLE IN GPM	GPA  20"							
			3 MPH	4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	
SJ3-015-VP (100) Green	20	0.11	10.9	8.2	6.5	5.4	4.1	3.3	2.7	
	30	0.13	12.9	9.7	7.7	6.4	4.8	3.9	3.2	
	40	0.15	14.9	11.1	8.9	7.4	5.6	4.5	3.7	
	50	0.16	15.8	11.9	9.5	7.9	5.9	4.8	4.0	
	60	0.17	16.8	12.6	10.1	8.4	6.3	5.0	4.2	
SJ3-02-VP (50) Yellow	20	0.14	13.9	10.4	8.3	6.9	5.2	4.2	3.5	
	30	0.17	16.8	12.6	10.1	8.4	6.3	5.0	4.2	
	40	0.20	19.8	14.9	11.9	9.9	7.4	5.9	5.0	
	50	0.21	21	15.6	12.5	10.4	7.8	6.2	5.2	
	60	0.22	22	16.3	13.1	10.9	8.2	6.5	5.4	
SJ3-03-VP (50) Blue	20	0.24	24	17.8	14.3	11.9	8.9	7.1	5.9	
	30	0.27	27	20	16.0	13.4	10.0	8.0	6.7	
	40	0.30	30	22	17.8	14.9	11.1	8.9	7.4	
	50	0.33	33	25	19.6	16.3	12.3	9.8	8.2	
	60	0.35	35	26	21	17.3	13.0	10.4	8.7	
SJ3-04-VP (50) Red	20	0.30	30	22	17.8	14.9	11.1	8.9	7.4	
	30	0.36	36	27	21	17.8	13.4	10.7	8.9	
	40	0.40	40	30	24	19.8	14.9	11.9	9.9	
	50	0.43	43	32	26	21	16.0	12.8	10.6	
	60	0.47	47	35	28	23	17.4	14.0	11.6	
SJ3-05-VP (50) Brown	20	0.36	36	27	21	17.8	13.4	10.7	8.9	
	30	0.45	45	33	27	22	16.7	13.4	11.1	
	40	0.50	50	37	30	25	18.6	14.9	12.4	
	50	0.55	54	41	33	27	20	16.3	13.6	
	60	0.59	58	44	35	29	22	17.5	14.6	
SJ3-06-VP (50) Gray	20	0.42	42	31	25	21	15.6	12.5	10.4	
	30	0.54	53	40	32	27	20	16.0	13.4	
	40	0.60	59	45	36	30	22	17.8	14.9	
	50	0.66	65	49	39	33	25	19.6	16.3	
	60	0.70	69	52	42	35	26	21	17.3	
SJ3-08-VP White	20	0.56	55	42	33	28	21	16.6	13.9	
	30	0.72	71	53	43	36	27	21	17.8	
	40	0.80	79	59	48	40	30	24	19.8	
	50	0.88	87	65	52	44	33	26	22	
	60	0.94	93	70	56	47	35	28	23	
SJ3-10-VP Lt. Blue	20	0.65	64	48	39	32	24	19.3	16.1	
	30	0.90	89	67	53	45	33	27	22	
	40	1.00	99	74	59	50	37	30	25	
	50	1.11	110	82	66	55	41	33	27	
	60	1.19	118	88	71	59	44	35	29	
SJ3-15-VP Lt. Green	20	0.99	98	74	59	49	37	29	25	
	30	1.24	123	92	74	61	46	37	31	
	40	1.50	149	111	89	74	56	45	37	
	50	1.68	166	125	100	83	62	50	42	
	60	1.83	181	136	109	91	68	54	45	
SJ3-20-VP Black	20	1.41	140	105	84	70	52	42	35	
	30	1.75	173	130	104	87	65	52	43	
	40	2.00	198	149	119	99	74	59	50	
	50	2.28	226	169	135	113	85	68	56	
	60	2.49	247	185	148	123	92	74	62	

Note: Always double check your application rates. See pages 153-157 for useful formulas and information.

NOTE: Always double check your application rates. See Pages 160 and 161 for useful formulas and information.