

PATENTED

"Manifold Stubby Valve"

FEATURES

- Stainless steel bolts.
- Glass filled polypropylene.
- Multiple design options.
- Unique patented compact design.
- Lightweight.
- Maximum operating pressure 100 P.S.I. @ 70°F. 75 P.S.I. @ 150°F.



2" Standard Port



PART NO.	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	PRICE
VSMT200CF	2" SP Flange X 2" Male NPT	100	2"	1 1/2"	53.70
VSF200CF	2" SP Flange X 2" Male Adapter	100	2"	1 1/2"	55.50

2" Full Port



PART NO.	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	PRICE
MVS220FP	2" FP Flange X 2" Female NPT	100	2"	2"	66.76
MVSF220FP	2" FP Flange X 2" Male Adapter	100	2"	2"	66.76
MVS220CF	2" FP Flange X 2" FP Flange	100	2"	2"	66.76

3" Standard Port



PART NO.	DESCRIPTION	MAX PSI	PIPE SIZE	OPENING THRU BALL	PRICE
MVSF300	3" Manifold Flange X 3" Male Adapter	100	3"	2 1/2"	136.48
MVSMT300	3" Manifold Flange X 3" Male NPT	100	3"	2 1/2"	142.13

VALVES